

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
phone +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



FERMANT COMPACT

The new FERMANT Compact series has been available is sealing lengths of 460 and 600 mm.

The devices were specifically design for use in a damp environment.

The degree of protection is comparable to IP 54 and even IP 65 for the foot switch.

The guarantees optimum protection against projected water from all directions.

The sealing device is manufactured from rustproof stainless steel throughout.

Owing to the large bar operating radius, it is also possible to seal bags with a large excess width. The bar opening of 80 mm allows easy insertion of the bags to be sealed.

Out tried and trusted digital control allows easy adjustment of the sealing parameters which therefore remain constant and are reproducible at any time.



TECHNICAL DATA



FERMANT COMPACT 460

Sealing length (mm)	460
Sealing width (mm)	4
Sealing bar opening (mm)	80
Max sealing output (mm)	2x0,40
Connected voltage	230V/50 Hz
Degree of protection (sealer)	IP 54
Degree of protection (pedal)	IP 65
Weight	Kg. 30
Dimension (mm)	450x260x320h

FERMANT COMPACT 600

Sealing length (mm)	600
Sealing width (mm)	4
Sealing bar opening (mm)	80
Max sealing output (mm)	2x0,40
Connected voltage	230V/50 Hz
Degree of protection (sealer)	IP 54
Degree of protection (pedal)	IP 65
Weight	Kg. 30
Dimension (mm)	830x320x260



Technical alteration without prior notice.