

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



HTMST 1000 LP

The HTM ST was specifically designed for sealing film sacks. The device is individually adjustable to the desired sack size a hand crank.

The sealing and cooling times are continuously adjustable. The sealing process is triggered by a foot contact switch.

The advantage to you:

The new sack sealing device with air suction has a special strip that holds the sack and renders it airtight during the aspiration process. Both hands therefore remain free for aligning the film sack.

HTM ST sealing device is used successfully wherever reducing the volume of a packaging as far as possible is involved or undesirable shaking movements in the packed goods is to be avoided. Our devices are used in almost all areas of industry: ranging from packing cushions, blankets, ground coffee or even wine corks to injection moulded components and high quality electronic components.

The HTMST is also available in stainless steel.



A richiesta /Optional

Stainless steel version
Modification on request

TECHNICAL DATA I



HTMST 1000 LP

Sealing length (mm)	1000
Sealing width (mm)	6
Bar opening (mm)Max.	30
Sealable film thickness (mm)	-
Connected voltage	400 V trifase, 50/60 Hz
Degree of protection	IP 54
Vacuum pump	140m ³ /h
Weight	Kg. 240
Dimension (mm)	1300x2100x1300



Technical alteration without prior notice.