

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



HTM

These film sealing devices are used wherever thick film material or long film width must be sealed. The range of application extends from sealing in of mattresses, including manufacture of hoods, to sealing of composite film for container liners.

The devices are manufactured tailored to the customer.

The sealing times can be continuously adjusted to any type of film. The sealing process is triggered by a foot control. The HTM device is also available in stainless steel.



Optional

Stainless steel version
Modification on request

TECHNICAL DATA



HTM 1000

Sealing length (mm)	1000
Sealing width (mm)	6
Film thickness	Any thickness
Connection	400V trifase/50-60 Hz
Weight	Kg. 170
Degrees of protection	IP 54
Dimension (mm)	1620x500x950h
Material	Any types of thermoplastic films



HTM 2000

Sealing length (mm)	2000
Sealing width (mm)	6
Film thickness	Any thickness
Connection	400V trifase/50-60 Hz
Weight	Kg. 220
Degrees of protection	IP 54
Dimension (mm)	2950x500x1000h
Material	Any types of thermoplastic films



Technical alteration without prior notice.