

**stanok**

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy  
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39  
[www.stanok.it](http://www.stanok.it) - [info@stanok.it](mailto:info@stanok.it)



## HZ a pedale

These lightweight heat sealing pliers can be used for the most diverse applications. The connecting cable 4,5 meters in length guarantees a wide radius of action. A special insulating material prevents uncomfortable handle temperatures. Handling comfort is maintained even at a working temperature of 250°C.

The heat sealing pliers are suitable for all paper and aluminium laminates. Depending on the material type and thickness, the temperature is continuously adjustable from 60°C to 250°C.



### **Optional**

Foot pedal  
Table clamp screws  
Protective cover  
Teflon coated version

## TECHNICAL DATA



### **HZ 200/ PTFE**

Sealing length (mm)	200
Sealing width (mm)	12
Range temperature	100-250°C
Connection	230V/50 Hz 115V/50 Hz (on request)
Power	250 V
Weight	Kg. 1,3
Materia	Laminated film, multylayer film, BOPP

### **HZ 300/ PTFE**

Sealing length (mm)	300
Sealing width (mm)	12
Range temperature	100-250°C
Connection	230V/50 Hz 115V/50 Hz (on request)
Power	250 V
Weight	Kg. 1,5
Materia	Laminated film, multylayer film, BOPP

### **HZ 400/ PTFE**

Sealing length (mm)	400
Sealing width (mm)	12
Range temperature	100-250°C
Connection	230V/50 Hz 115V/50 Hz (on request)
Power	250 V
Weight	Kg. 1,7
Materia	Laminated film, multylayer film, BOPP

### **HZ 500/ PTFE**

Sealing length (mm)	500
Sealing width (mm)	12
Range temperature	100-250°C
Connection	230V/50 Hz 115V/50 Hz (on request)
Power	250 V
Weight	Kg. 1,9
Materia	Laminated film, multylayer film, BOPP

NO POLYETHYLENE FILM



Technical alteration without prior notice