

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



KSZ

Suited to seal all thermoplastic films like polyethylene, PVC, Polypropylene as well as some thin heat.sealable laminated.

It is used for packing bulky machinery, control cabinet, measuring units, various small items etc. In filmbags, for manufacturing of water and air tight transport and seapacking, as well as for sealing of bags and sacks.



Optional

Foot pedal
Table clamp screws

TECHNICAL DATA



KSZ 300

Sealing length (mm)	300
Sealing width (mm)	3
Film thickness(mm)	2x0,20
Connection	230V/50 Hz
Power	250 W
Weight with impulse unit	5,25 Kg
Material	Thermoplastic film

KSZ 400

Sealing length (mm)	400
Sealing width (mm)	3
Film thickness(mm)	2x0,20
Connection	230V/50 Hz
Power	250 W
Weight with impulse unit	5,5 Kg
Material	Thermoplastic film

KSZ 500

Sealing length (mm)	500
Sealing width (mm)	3
Film thickness(mm)	2x0,20
Connection	230V/50 Hz
Power	250 W
Weight with impulse unit	5,8 Kg
Material	Thermoplastic film

KSZ 600

Sealing length (mm)	600
Sealing width (mm)	3
Film thickness(mm)	2x0,20
Connection	230V/50 Hz
Power	250 W
Weight with impulse unit	6 Kg
Material	Thermoplastic film



Technical alteration without prior notice.