

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



PS

Impulse sealers model PS are suitable for closing plastic bags up to 100 microns. Specific to protect any kind of object, liquid, solid or dust in plastic bags very user friendly PS series are indicated wherever plastic bags are used.

PS are always ready to use, it is enough to put the bag into the sealing jaws and push by hand for a few seconds the sealing bar to get you bag sealed.

The welding time can be regulated in according to the bag's gauge.

Model PS is available in 4 different sizes: cm. 20, 30, 40, 50



TECHNICAL DATA



PS 200

Seal seam length (mm)	200
Seal seam width (mm)	2
Film thickness (mm)	2x0,10
Connection	230V/50 Hz
Power	400 W
Weight	Kg. 2,6
Dimension (mm)	320x80x150h
Film	Polyetyilene , Polyproillene, PVC



PS 300

Seal seam length (mm)	300
Seal seam width (mm)	2
Film thickness (mm)	2x0,10
Connection	230V/50 Hz
Power	450 W
Weight	Kg. 4,3
Dimension (mm)	450x80x150h
Film	Polyetyilene , Polyproillene, PVC



PS 400

Seal seam length (mm)	400
Seal seam width (mm)	2
Film thickness (mm)	2x0,10
Connection	230V/50 Hz
Power	600 W
Weight	Kg. 5,4
Dimension (mm)	560x80x180h
Film	Polyetyilene , Polyproillene, PVC



PS 500

Seal seam length (mm)	500
Seal seam width (mm)	2
Film thickness (mm)	2x0,10
Connection	230V/50 Hz
Power	650 W
Weight	Kg. 6,4
Dimension (mm)	650x80x180h
Film	Polyetyilene , Polyproillene, PVC



Technical alteration without prior notice.