

stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39
www.stanok.it - info@stanok.it



SERIE H

The H devices are particularly suitable for sealing together film widths for garden pond films, greenhouse or swimming pool covers for example.

However, repairs of large film widths can also be performed with this device.

The devices can be used wherever the film to be sealed is only accessible from one side.

The H device allows mobile use, even in the garden and is very easy to operate.



TECHNICAL DATA



H 220

Sealing length (mm)	220
Sealing width (mm)	4
Film thickness (mm)	2x0,25
Connection	230V/50 Hz
Power	250 VA
Weight of sealing bar	Kg. 3,7
Weight of impulse unit	Kg. 7,8
Dimension of impulse unit (mm)	160x310x170h
Dimension of sealing bar (mm)	280x40x135h
Material	Polyethylene, polypropylene, PVC

H 280

Sealing length (mm)	280
Sealing width (mm)	4
Film thickness (mm)	2x0,25
Connection	230V/50 Hz
Power	250 VA
Weight of sealing bar	Kg. 3,8
Weight of impulse unit	Kg. 7,8
Dimension of impulse unit (mm)	160x310x170h
Dimension of sealing bar (mm)	340x40x315h
Material	Polyethylene, polypropylene, PVC

H 380

Sealing length (mm)	380
Sealing width (mm)	4
Film thickness (mm)	2x0,25
Connection	230V/50 Hz
Power	250 VA
Weight of sealing bar	Kg. 4
Weight of impulse unit	Kg. 7,8
Dimension of impulse unit (mm)	160x310x170h
Dimension of sealing bar (mm)	440x40x135h
Material	Polyethylene, polypropylene, PVC

H 580

Sealing length (mm)	580
Sealing width (mm)	4
Film thickness (mm)	2x0,25
Connection	230V/50 Hz
Power	250 VA
Weight of sealing bar	Kg. 4
Weight of impulse unit	Kg. 13
Dimension of impulse unit (mm)	200x310x170h
Dimension of sealing bar (mm)	640x40x135h
Material	Polyethylene, polypropylene, PVC



Technical alteration without prior notice.