

# stanok

via Liguria 34/18 - 20068 Peschiera Borromeo (Mi) - Italy  
telefono +39 02.55.30.58.59 - fax +39 02.51.68.71.39  
[www.stanok.it](http://www.stanok.it) - [info@stanok.it](mailto:info@stanok.it)



## SZ

The SZ film sealing pliers are successfully used wherever large, bulky goods, e.g for transport or warehousing, must be packed. The light weight makes the device easy to transport and guarantees fatigue-free work even over a prolonged period.



### Optional

Balancer  
Heating band on request

## DATI TECNICI



### SZ 100

Sealing length (mm)	100
Sealing width (mm)	4
Film thickness (mm)	2x0,40
Connection	230V/50 Hz
Power	250 VA
Weight with impulse unit	Kg. 10
Dimension (mm)	170x300x150h
Material	Polyethylene, Polypropylene, PVC

### SZ 220

Sealing length (mm)	220
Sealing width (mm)	4
Film thickness (mm)	2x0,40
Connection	230V/50 Hz
Power	250 VA
Weight with impulse unit	10,5
Dimension (mm)	290x300x150h
Material	Polyethylene, Polypropylene, PVC

### SZ 280

Sealing length (mm)	280
Sealing width (mm)	4
Film thickness (mm)	2x0,40
Connection	230V/50 Hz
Power	250 VA
Weight with impulse unit	Kg. 10,6
Dimension (mm)	350x300x150h
Material	Polyethylene, Polypropylene, PVC

### SZ 380

Sealing length (mm)	380
Sealing width (mm)	4
Film thickness (mm)	2x0,40
Connection	230V/50 Hz
Power	250 VA
Weight with impulse unit	Kg. 10,8
Dimension (mm)	450x300x150h
Material	Polyethylene, Polypropylene, PVC

### SZ 580

Sealing length (mm)	580
Sealing width (mm)	4
Film thickness (mm)	2x0,40
Connection	230V/50 Hz
Power	250 VA
Weight with impulse unit	Kg. 16
Dimension (mm)	650x300x150h
Material	Polyethylene, Polypropylene, PVC



Technical alteration without prior notice.